



AKFIX SPRAY PAINT

1 – DESCRIPTION

Akfix Spray Paint is designed for numerous application possibilities. Special spray system, which is even used by famous graffiti artists. Available in a broad range of the best-selling colours, mainly matching to RAL.

2 – PROPERTIES

- High-grade nitro-combi quality
- Very good coverage
- Excellent adhesion on many surfaces
- Good flow, smooth surface
- Quick-drying
- Suitable for indoors and outdoors applications
- Polishable surface
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- Quick-drying (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat).

3 – APPLICATIONS

- Suitable for wood, metal, paper, glass or paintable hard plastics as well as for many textiles for any variety of designing applications.
- Also applicable for the designing of finery, concrete and natural stone.

4 – INSTRUCTIONS

- The surface has to be clean, dry and free from fat.
- Remove residues of old paintings and rust, then sand and prime if necessary.
- Let dry for 1 - 2 hours.
- Use Plastic Primer on plastic parts.
- Cover areas not to be painted.
- Before use, shake the can for 3 minutes.
- Test spray at an invisible spot to check colour-matching and compatibility of the lacquer.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over synthetic paints!

5- STORAGE AND SHELF LIFE

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).

6- ENVIRONMENT AND LABELLING

Environmentally sound: The products are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".



Marking/Labelling: All products comply with the actual labelling regulations according to preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

7- TECHNICAL PROPERTIES

Basis	: Nitro-combi	
Color	: Diverse	
Smell	: Solvent	
Degree of gloss	: Glossy: 80 gloss units Matt: 5-10 gloss units	DIN 67530
Efficiency	: 0.8-1.5 m ² * (depending on colour) (400 mL)	
Drying time (20 °C and 50% R.H)	: Approx. 10 minutes (Dust-dry) Approx. 15 minutes (Non-sticky) Approx. 30 minutes (Dry to touch) Approx. 2 hours (Cured) Approx. 24 hours (Can be polished)	
Temperature resistance	: Up to 80°C	

* Depending on consistence and color.

8- COLOR TABLE

Art No	Color Code
422997	RAL 9005 gl.
423000	RAL 9005 mat
423017	RAL 9010 gl.
423024	RAL 3020 gl.
423031	RAL 5010 gl.
423055	silver
423109	RAL 7040 gl.
423116	RAL 8017
423123	RAL 9010 mat
423130	RAL 1023 gl.
423154	RAL 9006
423161	RAL 3002 gl.
423178	RAL 1015 gl.
423185	RAL 6001 gl.

9- DISCLAIMER

This application-technological information is given to the best of our knowledge. The notes mentioned herein are ,however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Akkim Sealants & Adhesives is not responsible for any false usage of the product.